

→ Reverse osmosis Direct flow

MYNDER 600GPD

(Ref.911060)

SPECIFICATIONS

MAXIMUM FLOW	1,8 lpm *
WEIGHT	12.45 kg
INLET TEMPERATURE (maxmin.)	38°C / 5°C
INLET TDS	1500 ppm
MAXIMUM HARDNESS RECOMMENDED	15 °F
INLET PRESSURE	4 bar - 2 bar (400kPA-200kPa)
PREFILTER	5 micron polypropylene and carbon high quality block
MEMBRANE	600GPD
FAUCET	Electric faucet
PUMP	High performance booster
POWER SUPPLY	24 VDC 2,5 A
EXTERNAL POWER ADAPTER	100V. 240 Vac 50/60Hz: 24Vdc 96W
DRAIN RESTRICTOR	Easy to access and clean



Inlet connection	3/8"
Faucet connection	1/4"
Drain connection	1/4"

CONSUMIBLES ORIGINALES

Combinated filter. (Ref. 911061)

Reverse osmosis membrane (Ref. 911062)

Prefiltro Starfit (Ref. 953002)



FILTER CONTROL



SOUND WARNINGS



LED STATUS



VERSATILITY



HIGH EFFICIENCY



PROGRAMMED START SYSTEM




ECO PACK



AUTO FLUSHING



NOT COMPATIBLE 3-WAY TAP











The marketing of water treatment equipment and household appliances, as well as the provision of non-regulated training related to the technology of the equipment marketed, are certified and comply with the UNE-ISC-9001 standard for WLG (B-60326279).







WLG (B-60326279) is a member of Aqua España, which belongs to Aqua Europa (Federation of European national associations).

^{*} Depending on the characteristics of the water to be treated.