→ Direct Flow Reverse Osmosis

RO KLEIN 800

(Ref.911027)

DESCRIPTION

Advanced direct flow equipment
Instant unlimited water
No accumulation tank
Electronic faucet
Water quality and filter useful life notice

CHARACTERISTICS

WEIGHT	16kg
FLOW	1.5/2 LPM
INLET TEMPERATURE	38°C - 5°C
TDS INPUT	1500ppm
INLET PRESSURE	1/4 bar 100 – 400 kPa
FILTER	Combined PP+active carbon
MEMBRANE	800 GPD
FAUCET	Smart faucet
PUMP	Booster
ELECTRICAL POWER SUPPLY	24 Vdc 95 W
EXTERNAL ELECTRICAL ADAPTER.	110 - 240V. 50/60Hz 24W.



Combi sediment + carbon filter (Ref. 910425) 800 GPD membrane (Ref. 911030)



CLICK



FILTER CONTROL



AQUASTOP



DIRECT FLOW



STATUS LED



HIGH PERFORMANCE ENGINE



CAPSULATED MEMBRANE




SMART FAUCET





385mm







WLG (B-60326279), is a member of the Water Quality Association.



The marketing of water treatment equipment and household appliances, as well as the design and delivery of non-regulated training related to the technology of the marketed equipment, are certified and comply with the UNE-150-9001 standard for WLG (B-60326279).



Associations).





WLG (B-60326279), has the granting of the authorization of Authorized Economic Operator (AEO), with the number ESAEOF18000008U6 and date of entry into force of the authorization 02/13/2018.