

→ Columbia Aqua

# FC 325 UF (Ref.796325)

## Ultrafiltration Water Dispensers

### FEATURES

TEMPERATURE	Cold - Hot
WORKING SYSTEMS	Ultrafiltration
COLD WATER TEMPERATURE	4 - 13 °C
COOLING CAPACITY	5 L/H
TEMPERATURE CONTROL	Thermostat
COLD WATER TANK CAPACITY	2 Liters
COLD WATER TANK MATERIAL	AISI 304 Stainless steel
COMPRESSOR	Sealed. Consumption 85W
COMPRESSOR REFRIGERANT	R - 134a
HOT WATER TANK CAPACITY	1 Liter
HOT WATER TEMPERATURE	80 - 85 °C
HEATING CAPACITY	3 L/H
HOT WATER INSTANT VOLUME	1,2 liters
HEATER TYPE	Stainless steel band system AISI 304. 400W Consumption
BOOSTER PUMP	No
WEIGHT	25 Kg
PRESENTATION	Top
WATER TREATMENT SYSTEM	5 µm 2,5 x 11,5 filter (x 1) 2,5 x 11,5 GAC filter (x 1) 2,5 x 11,5 UF cartridge (x 1) 2,5 x 11,5 Postfilter (x 1)




FILTRATION SYSTEM

FILTRATION AND  
ULTRAFILTRATION  
SYSTEM

COLD WATER PRODUCTION



HOT WATER PRODUCTION

WATER PRODUCTION AT  
ROOM TEMPERATURESECURITY SYSTEM FOR HOT WATER  
TO AVOID CHILDREN MANIPULATIONREVERSE OSMOSIS  
SYSTEM WITH PUMP  
FOR HIGHER PRODUCTIONMULTIFUNCTION  
INFORMATION SYSTEM BY LEDALKALINE FILTER  
PH ADJUSTER

WLG (B-60326279), is member of the  
Water Quality Association.



ACCREDITED BY ENAC  
Certif. nº 34/5200/14/0712

The trading of water treatment and household appliances as well as designing and teaching of non-official training courses related with its technology are certified and comply with the UNE-ISO-9001 far WLG (B-60326279).



WLG (B-60326279) is an Aqua España member, who belongs Aqua Europa (Federation of European nation associations).



WLG (B-60326279), has the rights granted for Authorized Economic Operator with number ESAEOF18000008U6 and 13/02/2018 as a date of entry of the authorization.