

WATER QUALITY NOTICE

→ Direct flow reverse osmosis

**RO JAVA 600** 

(Ref.910645)

## DESCRIPTION

5-stage equipment Installation kit Intelligent display High-performance membrane with self-washing Equipment without water tank Easy maintenance

## **SPECIFICATIONS**

PRODUCTION	1,6 LPM *
REJECTION FLOW RATE	1,02 LPM
CONVERSION	60%
INLET TEMPERATURE	40 ° C - 5 ° C
TDS INPUT	1500 ppm
INLET PRESSURE	2 / 4 bares 0,2 - 0,4 MPa
MEMBRANE	600 GPD
FAUCET	Special 1 way
PUMP	Booster
POWER SUPPLY	24 Vdc 120 W 5 A
EXTERNAL ADAPTER	185 - 240 V 50-60 Hz

\* Depending on the characteristics of the water to be treated.

## **ORIGINAL CONSUMABLES**

Polypropylene cartridge 5µm (Ref. 910681)
BLOCK Carbon replacement cartridge 10µm (Ref.910682)
High quality GAC Postcarbon replacement cartridge quality (Ref. 910683)
Membrane RO 600GPD (Ref.910685)

SECURITY SYSTEMS

11 months. Maintenance light warning system
12 months. Maintenance light warning system
15 months. Equipment lock for security, red light
Security system for hours of continuous operation. 3 hours computer lockout
Security system for hours of continuous operation. 80 hours computer lockout





WLG (B-60326279), is member of the Water Quality Association



ACREDITED BY ENAC Certif. nº 34/5200/14/0712

The trading of water treatment and The trading of water treatment and household appliances as well as designing and teaching of non-official training courses related with its technology are certified and comply with the UNE-ISO-9001 far WLG (B-60326279).



WLG (B-60326279) is an Aqua España member, who belongs Aqua Europa (Federation of European nation associations).



WLG (B-60326279), has the rights granted for Authorized Economic Operator with number ESAEOF18000008U6 and 13/02/2018 as a date of entry of the authorization.

