

WATER QUALITY NOTICE

445mm

150mm

PRESSURE PUMP

and yield

LED STATUS

AQUASTOP

Status indications

SECURITY LOCK

Guarantees the quality

Automatic leak detection leak detection system

Increased production

387mm

→ Direct flow reverse osmosis

RO PACÍFICA 800

(Ref.910646)

DESCRIPTION

5-stage equipment Installation kit Intelligent display High-performance membrane with self-washing Equipment without water tank Easy maintenance

SPECIFICATIONS

PRODUCTION	2 LPM *
REJECTION FLOW RATE	1,45 LPM
CONVERSION	58%
INLET TEMPERATURE	40 ° C - 5 ° C
TDS INPUT	1500 ppm
INLET PRESSURE	2 / 4 bares 0,2 - 0,4 MPa
MEMBRANE	800 GPD
FAUCET	Special 1 way
PUMP	Booster
POWER SUPPLY	24 Vdc 5 A
EXTERNAL ADAPTER	185 - 240 V 50-60 Hz

* Depending on the characteristics of the water to be treated.

ORIGINAL CONSUMABLES

Polypropylene cartridge 5µm (Ref. 910681)
BLOCK Carbon replacement cartridge 10µm (Ref.910682)

High quality GAC Postcarbon replacement cartridge quality (Ref. 910683)

Membrane RO 800GPD (Ref.910684)





WLG (B-60326279), is member of the Water Quality Association.



Certif, nº 34/5200/14/0712

The trading of water treatment and household appliances as well as designing and teaching of non-official training courses related with its technology are certified and comply with the UNE-ISO-9001 far WLG (B-60326279).



WLG (B-60326279) is an Aqua España member, who belongs Aqua Europa (Federation of European nation associations).



WLG (B-60326279), has the rights granted for Authorized Economic Operator with number ESAEOF18000008U6 and 13/02/2018 as a date of entry of the authorization.



QUALITY CONTROL

Conductivity control

Greater pure water flow

Automatic warning of

Membrane cleaning

FILTER CONTROL

maintenance FLUSHING READY

system

DOUBLE FLOW

Π

ß

X

11 months. Maintenance light warning system	
12 months. Maintenance light warning system	
15 months. Equipment lock for security, red light	
Security system for hours of continuous operation. 3 hours computer lockout	
Security system for hours of continuous operation, 75 hours computer lockout	