

→ UV LED 7L WITH HIGH GERMICIDAL POWER

KINGLIGHT UV LED 7 LPM

(Ref. 243618)

DESCRIPTION

Ideal equipment for the elimination of germs and microorganisms from water supplied by UV-C radiation.

CHARACTERISTICS

MAIN MATERIAL	PP, Aleación de aluminio
INPUT VOLTAGE	100V*240V 50/60Hz
OUTPUT VOLTAGE	24 Vdc 1A
WORKING TEMPERATURE	5°C - 50°C
PRESSURE	1 MPa
CONNECTIONS	3/8"
WORKING FLOW FILTERED WATER	2L/min
WORKING FLOW OSMOSIS WATER	7L/min
STERILIZATION RATE	≥99,9
SERVICE LIFE	> 3.000h
UV POWER	15W
GRADE WATER-PROOF	x7



GREEN
Waiting



BLUE
In operation



RED
End of useful life

FUNCTIONALITIES


Built-in flow switch.

It is activated when water flows and deactivated when water flow stops.

Does not heat the water.

Built-in LED status control.

For installations with 1/4" pipe, ask for the 3/8" - 1/4" reduction (Ref. 951014).



WLG (B-60326279), is member of the Water Quality Association.



ACREDITED BY **ENAC**
Certif. nº 34/5200/14/0712

The trading of water treatment and household appliances as well as teaching of non-official training courses related with its technology, are certified and comply with the UNE-ISO-9001 for WLG (B-60326279).



WLG (B-60326279) is an Aqua España member, who belongs Aqua Europa (Federation of European nation associations).



WLG (B-60326279), has the rights granted for Authorized Economic Operator with number ESAE0F18000008U6 and 13/02/2018 as a date of entry of the authorization.