

## → Softener

# RIDER

 (Ref.795238)


## FEATURES

RESIN VOLUME	25 liters
VESSEL	9x35
WORKING FLOW	1m <sup>3</sup> /h
PEAK FLOW	1,5m <sup>3</sup> /h
MAXIMUM HARDNESS	120°HF

HIGH EFFICIENCY	
SALT / REGENERATION	1,5 kg Salt
EXCHANGE CAPACITY	96°HFxm <sup>3</sup>


STANDARD	
SALT / REGENERATION	3,0 kg Salt
EXCHANGE CAPACITY	141°HFxm <sup>3</sup>

HIGH CAPACITY	
SALT / REGENERATION	6,3 kg Salt
EXCHANGE CAPACITY	175°HFxm <sup>3</sup>
MINIMUM FLOW	0,1m <sup>3</sup> /h
WORKING TEMPERATURE	4-35°C
WORKING PRESSURES	2,5- 8 bar
PRESSURE RATING	8 bar
ELECTRICAL CONNECTION	220V/50Hz-12VAC
RATED ELECTRICAL POWER	4 W
PROTECTION CLASS	TYPE III

HIGH EFFICIENCY: 96°HFxm <sup>3</sup>						
15°HF	25°HF	30°HF	35°HF	45°HF	55°HF	
6,40	3,84	3,20	2,74	2,13	1,75	

STANDARD: 141°HFxm <sup>3</sup>						
15°HF	25°HF	30°HF	35°HF	45°HF	55°HF	
9,40	5,64	4,70	4,03	3,13	2,65	

HIGH CAPACITY: 175°HFxm <sup>3</sup>						
15°HF	25°HF	30°HF	35°HF	45°HF	55°HF	
11,67	7,00	5,83	5,00	3,89	3,18	



WLG (B-60326279), is member of the Water Quality Association.



ACCREDITED BY ENAC  
Certif. nº 34/5200/14/0712

The trading of water treatment and household appliances as well as designing and teaching of non-official training courses related with its technology are certified and comply with the UNE-ISO-9001 far WLG (B-60326279).



WLG (B-60326279) is an Aqua España member, who belongs Aqua Europa (Federation of European nation associations).



WLG (B-60326279), has the rights granted for Authorized Economic Operator with number ESAE0F18000008U6 and 13/02/2018 as a date of entry of the authorization.