

## FT-Line 2

Two FT filters with 5 µm polypropylene filtration and GAC activated carbon + assembly kit and sink faucet.



Components



Suitable for domestic use and the catering sector.

### Composition:

- FT-82 5 µm filter.
- FT-88 silver carbon filter.
- 2 FT caps.
- Bracket.
- Sink faucet: Oslo model.
- 3/8" valve. Inlet connector 3/8"-3/8"-1/4".
- 3/8" tube set.
- 1 LPM flow restrictor.
- Fixing screws included.

### Specifications:

- Box dimensions: 375 x 360 x 125 mm.
- Weight: 2500 g.
- Max. pressure: 125 PSI / 8,6 bar.
- Max. flow.: 0,5 GPM / 1,9 LPM.
- Service life: 2000 GAL / 7560 l.
- Max. temperature: 100 °F / 38 °C.
- Min. temperature: 35 °F / 2 °C.

Code	Packaging units	Description
795451	1	Filtration module FT-Line 2

## FT-Line 3

Two FT filters and an ultrafiltration membrane + assembly kit and sink faucet.



Components



Suitable for domestic use.

### Composition:

- FT-82 5 µm filter.
- FT-83 carbon filter.
- FT-91 ultraFiltration.
- 3 FT Caps.
- Bracket.
- Sink faucet: Oslo model.
- 3/8" valve. Inlet connector. 3/8" tube set.
- 1 LPM flow restrictor. Fixing screws included.

### Specifications:

- Box dimensions: 405 x 425 x 130 mm.
- Weight: 3300 g.
- Max. pressure: 58 PSI / 4 bar.
- Max. flow.: 0,25 GPM / 1 LPM.
- Service life: 2000 GAL / 7560 l.
- Max. temperature: 100 °F / 38 °C.
- Min. temperature: 35 °F / 2 °C.

Code	Packaging units	Description
795450	1	FT-Line 3

## FT-Line 85

FT cation resin filter for water softening.

Suitable for vending use and the catering sector, in order to protect coffee-makers and hot water equipment.

### Composition:

- FT-85 cation resin filter.
- FT cap.
- Bracket.
- 2 x 3/8" quick-connectors.
- 0.5 LPM flow restrictor.
- Fixing screws included.

### Specifications:

- Box dimensions: 210 x 365 x 100 mm.
- Weight: 1200 gr.
- Max. pressure: 125 PSI / 8.6 bar.
- Max. flow: 0.150 GPM / 0.5 LPM.
- Service life: 160 GAL / 600 L. A 10 °HF.
- Max. temperature: 100 °F / 38 °C.
- Min. temperature: 35 °F / 2 °C.



Code	Packaging units	Description
795550	1	FT-Line 85



FT Line BASIC  
210 x 365 x 100  
mm **795554**  
**795556** **795558**  
**795550** **795557**



FT Line 1  
380 x 300 x 125 mm  
**795454**



FT Line 2  
375 x 360 x 125 mm  
**795451**



FT Line 3  
405 x 425 x 130 mm  
**795450**



FT Line PRE  
275 x 385 x 125 mm  
**795452**

## Spare Parts for FT Filters



Components

(Depending on model).



Code	Packaging units	Model	Dimensions   ø	Description	Specifications
545950	25	FT-82	9,5" 2,5"	5 µm polypropylene cartridge	Weight: 300 g Max. pressure: 125 PSI / 8,6 bar Max. flow.: 1 GPM / 3,78 LPM Service life: 1 year / 3000 GAL / 11340 l



Code	Packaging units	Model	Dimensions   ø	Description	Specifications
546750	25	FT-83	9,5" 2,5"	GAC activated carbon cartridge. Contains NSF carbon	Weight: 450 g Max. pressure: 125 PSI / 8,6 bar Max. flow.: 0,5 GPM / 1,9 LPM Service life: 1 year / 2000 GAL / 7560 l



Code	Packaging units	Model	Dimensions   ø	Description	Specifications
790350	25	FT-87	9,5" 2,5"	pH regulating cartridge and remineralizer	Weight: 700 gr. Max. pressure: 125 PSI / 8.6 bar Max. flow: 0.25 GPM / 1 LPM Service life: 1 year / 2600 GAL / 10000 L



Code	Packaging units	Model	Dimensions   ø	Description	Specifications
547551	25	FT-88	9,5" 2,5"	Silver activated carbon post-carbon cartridge. Bacteriostatic	Weight: 750 gr. Max. pressure: 125 PSI / 8.6 bar Max. flow: 0.25 GPM / 1 LPM Service life: 2600 GAL / 10000 L



Code	Packaging units	Model	Dimensions   ø	Description	Specifications
547552	25	FT-91	9,5" 2,5"	Ultrafiltration cartridge	Weight: 450 g Max. pressure: 58 PSI / 4 bar Max. flow.: 0,3 GPM / 1 LPM Service life: depending on water characteristics

## Spare Parts for FT Filters



Components



(Depending on model).



Code	Packaging units	Model	Dimensions l    ø	Description	Specifications
790353	25	FT-92	9,5" 2,5"	<b>BLOCK activated carbon cartridge.</b>	Weight: 500 g Max. pressure: 125 PSI / 8,6 bar Max. flow.: 1 GPM / 3,9 LPM Service life: 1 year / 1500 GAL / 5670 l



Code	Packaging units	Model	Dimensions l    ø	Description	Specifications
790352	25	FT-85	9,5" 2,5"	<b>Cation resin cartridge for water softening</b>	Weight: 600 g Max. pressure: 125 PSI / 8,6 bar Max. flow.: 0,15 GPM / 0,5 LPM Service life: 100 GAL / 600 l a 10 °HF



Code	Packaging units	Model	Dimensions l    ø	Description	Specifications
790351	25	FT-89	9,5" 2,5"	<b>Mixed bed resin cartridge for demineralization</b>	Weight: 500 g Max. pressure: 125 PSI / 8,6 bar Max. flow.: 0,15 GPM / 0,5 LPM Service life: 600 GAL / 2000 l a 5ppm de TDS



Code	Packaging units	Model	Dimensions l    ø	Description	Specifications
547554	25	FT-90	9,5" 2,5"	<b>Post-carbon cartridge + PH increaser</b>	Weight: 460 gr. Max. pressure: 125 PSI / 8.6 bar Max. flow: 0.25 GPM / 1 LPM Service life: 2600 GAL / 10000 L



Code	Packaging units	Model	Dimensions l    ø	Description	Specifications
547550	25	FT-86	9,5" 2,5"	<b>Activated carbon post-carbon cartridge. Contains NSF carbon</b>	Weight: 500 g Max. pressure: 125 PSI / 8,6 bar Max. flow.: 0,5 GPM / 1,9 LPM Service life: 1 year / 1500 GAL / 5670 l

## Spare Parts for Ft Filters



Code	Packaging units	Dimensions mm.	Description
749602	1	100x75	Wall bracket for 1 Ft filter



Code	Packaging units	Dimensions mm.	Description
749603	1	200x75	Wall bracket for 2 FT filters



Code	Packaging units	Dimensions mm.	Description
749604	1	290x75	Wall bracket for 3 FT filters

## Spare Parts for Ft Filters



Code	Packaging units	Description
752900	1	Flow restrictor 0,3 LPM insert type. Tube 3/8"
752902	1	Flow restrictor 1,0 LPM insert type. Tube 3/8"
752904	1	Flow restrictor 3,0 LPM insert type. Tube 3/8"



Code	Packaging units	Description
749650	1	Cap for FT filter with F thread connection 1/4"

