

→ Cold, hot, ambient and sparkling water dispenser equipped with reverse osmosis.

Columbia Aqua Juman

(Ref. 796797)

CHARACTERISTICS

COLD WATER	5 l/h
HOT WATER	5 l/h
WATER WITH GAS	5 l/h
CAP. COLD WATER TANK	2 liters
CAP. HOT WATER TANK	Tankless, instantaneous heating.
CAP. CARBONATING RESERVOIR	1 liter
REFRIGERATION SYSTEM	Heat pump. Cooling in tank.
COMPRESSOR POWER	70 W
REFRIGERANT GAS	R600a
COLD WATER TEMPERATURE	5°C - 10°C
HEATING POWER	2100 W
CUSTOMER WATER TEMPERATURE	45°C ~ 85°C
GERMICIDAL SYSTEM	UV led lamp inside the tank and at water outlets.
LEAKAGE PROTECTIONS	AQUASTOP leak sensor included
MEMBRANE FLUSHING	Includes automatic membrane flushing to extend membrane life.
INLET WATER PRESSURE (MAX~MIN)	3 ~ 1 BAR
INLET WATER TEMPERATURE (MAX~MIN)	38°C ~ 5°C
CONNECTIONS	1/4" inlet- 1/4" drain
WEIGHT	18,5 KG



Ref. 796802 Juman combined filter - Polypropylene / carbon.

Ref. 796803 Membrane MRO 110 SPD





TACTILE PUSH BUTTONS



INDICATOR OF TEMPERATURES




FAST CONNECTIONS AND MAXIMUM SECURITY



FORCED VENTILATION SYSTEM



DESKTOP UNIT







WLG (B-60326279), is member of the Water Quality Association.



The trading of water treatment and household appliances as well as designing and teaching of non-official training courses related with its technology are certified and comply with the UNE-ISO-9001 far WLG (B-60326279).







WLG (B-60326279) is an Aqua España member, who belongs Aqua Europa (Federation of European nation associations).