

→ Water softener


DENVER BLUE 12

(Ref.960183)

CHARACTERISTICS

RESIN VOLUME	12 litres	
WORK FLOW-RATE	0,5 m³/h	
MAXIMUM FLOW-RATE	0,8 m³/h	
LOW CAPACITY CONFIGURATION		An
SALT/ REGENERATION	0,5 kg salt	
EXCHANGE CAPACITY	40°HFxm ³	
MEDIUM CAPACITY CONFIGURATION		
SALT/ REGENERATION	1 kg salt	
EXCHANGE CAPACITY	49°HFxm³	$\left(\begin{array}{c} \text{Sal} \\ \text{\tiny NaCl} \end{array} \right)$
		\smile
HIGH CAPACITY CONFIGURATION		E SP FRA ENG
SALT/ REGENERATION	1,5 kg salt	ENG
EXCHANGE CAPACITY	60°HFxm³	
TEMPERATURE RANGE	4-35°C	
PRESSURE RANGE	2,5- 8 bar	
PRESSURE CLASSIFICATION		
ELECTRICAL CONNECTION	220V/ 50Hz -12VAC	
RATED ELECTRICAL POWER	4W	









WLG (B-60326279), is member of the Water Quality Association.



The trading of water treatment and household appliances as well as designing and teaching of non-official training courses related with its technology are certified and comply with the UNE-ISO-9001 far WLG (B-60326279).

ELECTRONIC PROGRAMMER

VOLUMETRIC

INTEGRATED BY-PASS

ELECTRONIC ADAPTER

EASY SALT FILLING

MULTILINGUAL PROGRAMMER

MIXING VALVE



WLG (B-60326279) is an Aqua España member, who belongs Aqua Europa (Federation of European nation associations).



WLG (B-60326279), has the rights granted for Authorized Economic Operator with number ESAEDF18000008U6 and 13/02/2018 as a date of entry of the authorization.