

→ RO Domestic compact with pump

## **RO WYKA PUMP**

(Ref. 733002)

## **DESCRIPTION**

5-stage team
With pump
Equipment with water tank
Easy installation
Easy maintenance

## **SPECIFICATIONS**

WEIGHT	13,5 kg
FLOW	0,2 LPM
INLET TEMPERATURE	40 ° C - 2 ° C
INLET TDS (max).	2000 ppm
INLET PRESSURE	2,5 bar - 1 bar (250-100 kPa)
FAUCET	Mini Robin
TANK	5,5 L
PUMP	UP 7000
POWER SUPPLY	24 Vdc 1,1 A
EXTERNAL ADAPTER	10 - 240V, 50/60Hz, 24Vdc

## **ORIGINAL CONSUMABLES**

CS Granulated Carbon Filter (Ref.291902)	
Sediment pre-filter (Ref.291803)	
Remineralizing post-filter (Ref.790102)	
Encapsulated membrane 50 GPD GREENFILTER (Ref. 717701)	



QUALITY CARBON



REMINERALIZER



INSERT



SOLENOID VALVE



ELECTRONIC ADAPTER



DIRECT ACCESS



PRESSURE PUMP




PRESSURE CONTROL



ENCAPSULATED MEMBRANE









WLG (B-60326279), is member of the Water Quality Association.



The trading of water treatment and household appliances as well as designing and teaching of non-official training courses related with its technology are certified and comply with the URE-ISO-9001 far WLG (B-60326279).







WLG (B-60326279) is an Aqua España member, who belongs Aqua Europa (Federation of European nation associations).